



VAPPRO VCI-826-S SHRINK FILM

NATO STOCK NUMBER:
6850-32-086-9421

The Panacea For Protecting & Packaging Large And Irregularly Shaped Equipment Against Corrosion

**Passed German VIA
(Vapour Inhibition Ability)
Test TL 8135-002**

DESCRIPTION

Vapro VCI-826-S is a VCI shrink film with exceptional rugged features designed for protecting and packaging large and irregularly shaped equipment against corrosion during storage of shipment.

Its UV's stabilization feature provides extended life to the film, making it ideal for use in outdoor storage and export environments. It is available in extra wide widths, for nearly any size requirement.

Vapro VCI-826-S shrink film is fortified with vapour corrosion inhibitor and is designed to be an alternative to expensive multi-layer laminated flexible structures and eliminates the need for vacuum packaging and dehumidification.

Vapro VCI-826-S keeps packaged metal clean, dry, and corrosion-free. The thick, heat-sealable, puncture-resistant, flexible VCI shrink film conforms easily to the shape of the equipment.

It is manufactured under strict ISO 9001-2008 norms, SP-VCI and is completely nitrite-free. It does not contain substances which are considered as dangerous to the health, neither in the production phase of the film, nor in the use of the end product (Certified for compliance with RoHS). It can be recycled both as material and as energy.

HOW VAPPRO 826-S WORKS

Vapro VCI-826-S emits VCI Vapour chemicals into the surrounding enclosure. The released vapour deposits on the metal surface and forms a protective mono-ionic layer which provides protection to the packaged parts from corrosion. It thus enables effective and long term protection of ferrous and non-ferrous metals against corrosion /oxidation and tarnishing under adverse conditions including contaminants in air such as hydrogen sulphide, sulphur dioxide, ammonia or acid rain. Vapro VCI vapors easily migrate to hard to reach areas like drilled holes, crevices etc. and give effective protection.

Metals protected:

- Aluminum
- Galvanized Steel
- Carbon Steel
- Brass
- Stainless Steel
- Silver
- Copper
- Solder



FEATURES & BENEFITS

- Multi-metal corrosion protection.
- UV Protection & Flame retardant properties.
- Extra strength & resistance to puncture and tear.
- High shrink force for broad application.
- Shrink wrap below the pallet not affected by forks.
- Extra protection for outdoor storage and export shipments.
- Six-sided protection is possible
- Immediate use of protected object (vehicle, equipment, etc.) upon removal.
- Vapro VCI-826S fits more tightly around objects, reducing or eliminating wear and tear in windy conditions. The plastics can be welded together onsite through the use of the same handheld heat guns used to shrink the films, it offers barriers to water, dust, vermin and other contaminants.
- It protects metals both through direct contact and vapour action.
- It keeps the load secure and keeps out dust, dirt, moisture, and contaminants.
- It provides wide-width, heavy duty, outdoor barrier packaging.
- Faster and more cost-effective to store equipment outdoors than put it under-roof.
- Plus on-site installation. Complete turnkey service.
- Reduces Shipping , Labor And Material Costs.

TYPICAL APPLICATIONS

- Irregularly shaped equipment that is difficult to wrap and move.
- Effectively protects equipment in storage or in transit.
- Preservation of Military vehicles, Weapons and equipment
- Mothball preservation of industrial equipment
- Export packaging of expensive larger equipment.
- Heavy equipment covers
- Seasonal equipment
- Excess Inventory
- Large Machine Parts
- Preservation of Recreational vehicles (boats, snowmobiles, etc.).
- Packaging of Crankshaft, Camshaft, Valves, Piston, Computer Instruments.
- Machinery Components, etc.

DIRECTIONS FOR USE

1. Ascertain the dimensions of equipment and determine amount of film required, ensure to make provision of at least 10 to 12" for overlap at all seams.
2. Place or arrange film in a clean and dry area.
3. Place equipment on film and ensure all sharp edges and corners are padded.
4. Wrap film around equipment and cautiously apply heat on Vapro VCI-826-S and it will shrink to desired fit.

TYPICAL PROPERTIES

Film Thickness
150µ

Colour
Blue

Typical Shrink Temperature Range
340-400°F

Typical Sealing Temperature Range
240-310°F

SHELF LIFE

Shelf Life : 36 months from date of manufacture
Protection Duration : 24 months

Magna

Magna International Pte Ltd

10H, Enterprise Road,
Singapore 629834.

Tel (65) 6786-2616

Fax (65) 6785-1497

Email info@magnachem.com.sg
info@vaprovci.com

Web http://www.vaprovci.com

Headquarters



Regional Offices



Follow us on social media for regular updates and news.  <https://www.facebook.com/vaprovci/>
<https://www.facebook.com/MagnaInternationalPteLtd/>

The details of our products are given completely free of undertaking. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.



Copyright 2018. Magna International Pte Ltd.
Magna, Vapro VCI and Vapro VBCI are registered trademarks of Magna International Pte Ltd.